

COUPLING SPACERS | Inside Diameter Coupling Spacers

- Connect Main and Tender (or Helper) Springs
- Inside Diameter Coupling Spacers for our Most Popular ERS Doublespring Applications
- Lightweight and Durable Anodized Aluminum Design
- CNC Precision Machined for Accuracy



Part Number	Quantity	Spring Diameter Range	
		inch	mm
Coupling Spacer (ID locating main to helper/tender)			
SPACER188	1	1.88	48
SPACER225	1	2.25	57
SPACER250	1	2.50	64
SPACER300	1	3.00	76
SPACER375	1	3.75	95
1-60-00	1	2.36	60
1-70-00	1	2.76	70

SPRING PERCH ADAPTER | 60mm to 2.50 inch

- Extend Your Range of Available Spring Rates
- Adapts 60mm to 2.50 inch ID SAE Springs
- Lightweight and Durable Anodized Aluminum Design
- CNC Precision Machined for Accuracy



Part Number	Quantity	Spring Diameter Range	
		inch	mm
Adapter			
ADAPTER60-250 (Perch Adapter 60mm to 2.50")	1	60 / 2.50	60 / 64

TORSION RELEASE BEARING – TRB | Smoother Deflection

- Reduce Torsional Binding by Removing Friction During Deflection
- Smoother and More Consistent Spring Action Throughout the Entire Range of Deflection
- Allows For Easier And More Precise Ride Height Adjustment by Eliminating Spring Seat Friction



Part Number	Quantity	Spring Diameter Range	
		inch	mm
Torsion Release Bearing			
TRB188	1	1.88	48
TRB200	1	2.00	51
TRB225	1	2.25	57
TRB250	1	2.50	64
TRB300	1	3.00	76